


ORDER BY CODE



1. Select Model Case & Connection Size.
2. Select Pressure Range.
3. Select Mounting Type If Other Than Standard Bottom Connection.
4. Add Choice Of Filling If Appropriate.
5. Add Special Configuration If Required.

EXAMPLE 1: MODEL 40S-100-FP-GF

4" 316ss Case, 1/4"NPT, Lower Back ss Conection, Front Flange Panel Mount, 0-100 psi, Glycerin Filled.

| Model | Dial Range Code | Mounting Type | Filling Type | Non Standard Requirements |
|-------|-----------------|---------------|--------------|---------------------------|
| 40S | 100 | FP | GF | None |

EXAMPLE 2: MODEL 41S-10K

4" 316ss Case, 1/2"NPT, Standard ss Conection, 0-10000 psi.

| Model | Dial Range Code | Mounting Type | Filling Type | Non Standard Requirements |
|-------|-----------------|---------------|--------------|---------------------------|
| 41S | 10K | None | None | None |

EXAMPLE 3: MODEL 20S-30-LB-GF-B

2.1/2" 316ss Case, 1/4"NPT, Lower Back ss Conection, 0-30 psi /Bar Dual Scale, Glycerin Filled.

| Model | Dial Range Code | Mounting Type | Filling Type | Non Standard Requirements |
|-------|-----------------|---------------|--------------|---------------------------|
| 20S | 30 | LB | GF | B |

PRESSURE

| Code | Range (psi) |
|------|-------------|
| 03 | 0-3 |
| 05 | 0-5 |
| 06 | 0-6 |
| 10 | 0-10 |
| 15 | 0-15 |
| 30 | 0-30 |
| 60 | 0-60 |
| 100 | 0-100 |
| 160 | 0-160 |
| 200 | 0-200 |
| 300 | 0-300 |
| 400 | 0-400 |
| 600 | 0-600 |
| 800 | 0-800 |
| 1K | 0-1000 |
| 1500 | 0-1500 |
| 2K | 0-2000 |
| 3K | 0-3000 |
| 4K | 0-4000 |
| 5K | 0-5000 |
| 6K | 0-6000 |
| 10K | 0-10000 |
| 15K | 0-15000 |
| 20K | 0-20000 |
| 30K | 0-30000 |
| 35K | 0-35000 |
| 50K | 0-50000 |
| 60K | 0-60000 |
| V30 | VAC 30-0 |
| R315 | REC 3-15 |
| C15 | COMP 30+15 |
| C30 | COMP 30+30 |
| C60 | COMP 30+60 |
| C100 | COMP 30+100 |
| C160 | COMP 30+160 |
| C200 | COMP 30+200 |
| C300 | COMP 30+300 |

INCHES of WATER COLUMN

| Code | Range (psi) |
|---------|-------------|
| 16"WC | 0-6" |
| 10"WC | 0-10" |
| 16"WC | 0-16" |
| 25"WC | 0-25" |
| 30"WC | 0-30" |
| 40"WC | 0-40" |
| 60"WC | 0-60" |
| 100"WC | 0-100" |
| 160"WC | 0-160" |
| 200"WC | 0-200" |
| 250"WC | 0-250" |
| V6"-0 | VAC 6"-0 |
| V10"-0 | VAC 10"-0 |
| V16"-0 | VAC 16"-0 |
| V25"-0 | VAC 25"-0 |
| V40"-0 | VAC 40"-0 |
| V60"-0 | VAC 60"-0 |
| V100"-0 | VAC 100"-0 |
| V160"-0 | VAC 160"-0 |
| V200"-0 | VAC 200"-0 |
| V250"-0 | VAC 250"-0 |

OUNCE

| Code | Range (psi) |
|-------|-------------|
| 10oz | 0-10oz |
| 16oz | 0-16oz |
| 32oz | 0-32oz |
| 40oz | 0-40oz |
| 60oz | 0-60oz |
| 100oz | 0-100oz |
| 160oz | 0-160oz |



We manufacture a wide range of instruments to customer's special requirements
We shall be pleased to discuss and advise on your specifications.

Specifications and dimensions given in this leaflet represent the state of engineering at the time of printing.
Engineering modifications may take place without prior notice.

STEWARTS - USA
6786 Tipperary
HOUSTON, TX 77061 USA
Phone. 713-643-1022
Fax. 713-643-2855
Toll Free. 1-800-901-1316
Web. stewartsusa.com